



The Siebold Company, Inc.



DGM Angle Bar / Slitter / Web Realignment System

Designed for mounting on a wide variety of presses, including the DGM 430, 440, 850, Advantage II, Goss Community®, and Urbanite® printing units.

FEATURES

- Designed for mounting on a wide variety of presses, including the DGM 430, 440, 850, Advantage II, Goss Community®, and Urbanite® printing units.
- Assembly is self contained with integral mounted low pressure air blower.
- Air bars are plumbed in 3 zones facilitating air flow shut-off control to unused sections.
- Pneumatic slitter cuts against a web driven hardened steel roller.



DGM Angle Bar / Slitter / Web Realigner

OPTIONS

- Additional Compensators for slit webs

SPECIFICATIONS

General

Model: DGM Angle Bar / Slitter/ Web Realignment System

Service Requirements & Connections

Electrical: 120V/60Hz/1 PH

Operational

- Angle bars are all 2 1/4" diameter polished hard chrome plated
- Can be configured for 35" or 36" web widths units.
- Minimum width of full web is 30", slit into 20" and 10" ribbons.
- Maximum width of full web is 36", slit into 24" and 12" ribbons. Operator or gear side of the full web can slit off into the 1/3 ribbon.
- Exiting 1/3 ribbon can be placed on the operator or gear side, above or below the 2/3 ribbon.